

GOVERNMENT OF TELANGANA



COMMON SCHEDULE OF RATES AS PER T.S STANDARD DATA FOR THE YEAR 2021-22 (Effective from 1st June 2021)

BOARD OF CHIEF ENGINEERS

Sl. No	ITEM CODE	DESCRIPTION OF THE ITEM	UNIT	Scheduled Rate for 2021-22
		mitre cut at two corners and joined with 2nos. of 150mm long brackets of 15x15mm M.S. square tube. The two vertical door profiles are to be reinforced with 19x19mm M.S. Square tube of 19 gauge. The door frame shall be fixed to the wall using 65/100mm long M.S. Screws through the frame by using PVC fasteners. A minimum of 4nos. of screws to be provided for each vertical member & minimum 2nos. for horizontal member etc. complete as per manufacturers specification and direction of Engineer-in-Charge for finished item of work		
482	TBSC-L.I-04	SUPPLY & FIXING SINGLE SIDE PRELAM SOLID PANEL PVC DOOR FRAME (CHOUKHAT) Providing and fixing factory made Pac single side Prelam door frame of the size 50X47 mm with a wall thickness of 5mm, made out of extruded 5mm rigid Pac single side prelam sheet, meter cut at two corners and joined with 2nos. of 150mm long brackets of 1515mm MS. Square tube. The two vertical door profiles are to be reinforced with 19X19mm MS. square tube of 19guage. The door frame shall be fixed to the wall using 65/100mm long MS. Screws through the frame by using Pac fasteners. a minimum of 4nos. of screws to be provided for each vertical member and minimum 2nos. for horizontal member etc. complete as per manufacture specification and direction of Engineer-in-charge.	1 Rm	330.00
483	TBSC-L.I-05	Supply and fixing of door frame made of hollow extruded PVC section having dimensions of 40 X 57mm with the wall thickness of 2mm +/- 0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2 corners shall be metre-cut/ welded. PVC DOOR FRAME	1 RM	256.00
484	TBSC-L.I-06	Supply and fixing of door frame made of hollow extruded PVC section having dimensions of 40 X 47 mm with the wall thickness of 2mm +/- 0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2 corners shall be mitre cut/welded	1 RM	202.00
485	TBSC-L.I-07	Supply & fixing of Door frames made of all formed sections of 1.25mm thick CRCA section, size should be 50x60mm with 32mm rebate. The corner of the frame should be welded. The frame should be painted with one coat of primer and finished painted with pure polyester paint. The frame should be provided with approved quality butt hinges of 3 Nos. complete for finished item.: Single	1RM	214.00

Sl. No	ITEM CODE	DESCRIPTION OF THE ITEM	UNIT	Scheduled Rate for 2021-22
		smooth operation and the system is to be installed at the site using anchor fasteners, silicon rubber sealant, easy glazing/ deglazing at site etc., including cost and conveyance of all materials, accessories, labour charges for transportation, erection at site complete for finished item of work.		
535	TBSC-L.III-13	Supplying and fixing door shutter, with shutter frame and infill panel made from PVC material conforming to IS: 10151-1982, the shutter frame made out of PVC extruded sections having overall dimension of 47 mm x 33 mm with wall thickness of 1.2mm + 0.3mm with usual process variation, the shutter frame with tapered shape to provide better grip to the infill panel end to drain out the water The Infill panel is made out of PVC Sections having Overall Dimensions of 200 mm x 20 mm with wall thickness of 1mm + 0.2mm, the shutter frames mitre cut and joined at the corner, by providing Polymeric “L” type corners to take hardware & fixtures fixed with 10-20mm counter sunk fully threaded parallel shank steel screws, all the hardware locations reinforced with special polymeric bars as per drawings, stickers showing locations of different hardware pasted on the shutter, the infill panels joined by tongue and groove method.	1 Sqm	1,007.00
536	TBSC-L.III-14	Supply and fixing of door shutters made of rigid PVC extruded hollow section(Nandi or equivalent) of 20mm X 200 mm with the wall thickness of 1.0mm +/- 0.1mm equally divided into 4 no's with tongue and groove locking arrangements. The shutter frame is made of 30mm X 79mm with the wall thickness of 1.5mm +/-0.15mm section mitre-cut and joined at 4 corners with 125mm X 225mm plastic brackets. The shutter shall be horizontally reinforced with 2 no's of 8mm PVC rods. Teak wood batons shall be reinforced inside the door shutter during the fabrication of the door shutter at those points wherever the hardware is fixed onto the door shutter.	1 Sqm	1,866.00
537	TBSC-L.III-15	Providing & fixing 30 mm thick solid panel PVC door shutter consisting of frame made out of 19 gauge M.S tube of 19 x 19 mm for stiles, top & bottom rail, with a coat of primer of approved make. M.S. Frame covered with 5 mm thick heat moulded PVC “C” channel of size of 30 x 50 mm forming stiles, 5 mm thick 75 mm wide PVC sheet for top, lock & bottom rail on either side 20 mm wide cross PVC sheet as gap insert for top &	1 Sqm	2,939.00