




2018-2019 ನೇ ಸಾಲಿನ ದರವೃತ್ತ
ಲೋಕೋಪಯೋಗಿ, ಬಂದರು ಮತ್ತು
ಒಳನಾಡು ಜಲಸಾರಿಗೆ ಇಲಾಖೆ,
ಬೆಂಗಳೂರು ವೃತ್ತ, ಬೆಂಗಳೂರು



SCHEDULE OF RATES 2018-2019
PUBLIC WORKS, PORTS & INLAND WATER
TRANSPORT DEPARTMENT
BENGALURU CIRCLE, BENGALURU

ಕರ್ನಾಟಕ ಸರ್ಕಾರ



ಲೋಕೋಪಯೋಗಿ, ಬಂದರು ಮತ್ತು
ಒಳನಾಡು ಜಲಸಾರಿಗೆ ಇಲಾಖೆ
ಬೆಂಗಳೂರು ವೃತ್ತ, ಬೆಂಗಳೂರು
2018-19ನೇ ಸಾಲಿನ ದರಗಳ ಪಟ್ಟಿ

**PUBLIC WORKS, PORTS & INLAND
WATER TRANSPORT DEPARTMENT
BENGALURU CIRCLE, BENGALURU
2018-19 SCHEDULE OF RATES**

Sl. No.	Description	Unit	Rate	
			Rs.	Ps.
	Sealed to the styles & rails with PVC Designer beading on either side & joined together with solvent cement adhesive etc., Complete as per manufacturers specification & direction of Engineer-in-charge fixed to frames with 3 nos of 75mm. Aluminium hinges.			
9.85.1	-do- with both side prelam	Sqm	3,746.00	
9.85.2	-do- with one side prelam	Sqm	2,798.00	
9.86	PVC DOOR SHUTTER : Supply and fixing of door shutters made of rigid PVC extruded hollow section of 20mm x 200mm with the wall thickness of 1.0mm + /0.1mm equally divided into 4nos with tongue and groove locking arrangements. The shutter frame is made of 58x24 mm with the wall thickness of 1.5mm+/-0.15mm section metricut and joined at 4 corners with 125mmx225mm plastic brackets. The shutter shall be horizontally reinforced with 2nos of 8mm PVC rods. Teak wood battons shall be reinforced inside the door shutter during the fabrication of the door shutter at those points wherever the hardware is fixed on to the door shutter.	Sqm	1,785.00	
9.87	Supply and fixing of door shutters made of rigid PVC extruded hollow section (Nandi or equivalent) of 20mmx200mm with the wall thickness of 1.0mm+/-0.1mm equally divided into 4nos with tongue an groove locking arrangements. The shutter frame is made of 30mm x 79mm with the wall thickness of 1.5mm+/-0.15mm section metric cut and joined at 4 corners with 125mmx225mm plastic brackets. The shutter shall be horizontally reinforced with 2nos of 8mm PVC rods. Teak wood battons shall be reinforced inside the door shutter during the fabrication of the door shutter at those points wherever the hardware is fixed on to the door shutter.	Sqm	2,000.00	
9.88	Supply and fixing of door frame made of hollow extruded PVC Section having dimension of 40x57mm with the wall thickness of 2mm+/-0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2 corners shall be metric cut/welded.	m	250.00	
9.89	Supply and fixing of door frame made of hollow extruded PVC Section having dimension of 40x46mm with the wall thickness of 2mm+/-0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2 corners shall be metric cut/weilded .	m	250.00	
9.90	Providing and fixing factory made splendoor of solid core single leaf rigid composite polymer laminated sal wood , door shutter of required thickness, manufactured out of solid core door conforming to IS 2202 (Part-1) 1991, laminated with 0.8 mm thick polymer, termite, water resistant and fire retardant with superior gluing based on vacuum lamination technology and with various pre moulded design on both faces conforming to IS 6307-1985, using adhesive conforming to IS 4835-1979 and door shutters tested in conformation to IS 4020-1994. The finish of shutters will be TEAK/CEDAR/ROSE WOOD/WALNUT, plain colours WHITE/IVORY/BEIGE/LIGHT GREY. Excluding cost of fixtures and inclusive of supply of shutters to respective work spot.			